

Product summary

- Wireless connection (IEEE 802.11b/g) eliminates the need to connect any cables between the display and a PC.
- High-speed wireless transmission produce smooth motion images.
- Images from one PC can be displayed in real-time on as many as eight displays.
- Images from up to 16 PCs can be simultaneously displayed onto a single screen.
- Plasma displays can be controlled using a Web browser.
- The Wireless Presentation Board also accepts component video and audio inputs.

Product specification (Design and specifications subject to change without notice)

Mass (Weight)	approx. 500 g
Slot No.	2slots model : Slot 1+Slot 2 3slots model : Slot 1+Slot 2, Slot 2+Slot 3
Compliant	IEEE802.11b/g
Frequency band	2412~2472 MHz (1~13 channels)
Country	France, Germany, Spain, Portugal, Netherlands, Belgium, Luxembourg, Denmark, Greece, Sweden, Finland, Austria, Italy, Czech, Hungary, Poland, Slovakia, Slovenia, Cyprus, Estonia, Latvia, Lithuania, Malta, Iceland, Switzerland, Norway, UK, Ireland Japan, Hongkong, Malaysia, Singapore, Thailand, Australia, New Zealand, Turkey, Egypt, Saudi Arabia, UAE

- Accessories
- Terminal function label (1 sheet)
 - Terminal board replacement instructions
 - Slot cover fixing screw (x4)
 - Remote control (x1)
 - Dry batteries (AA x2)
 - CD-ROM (x1)
 - Wireless LAN card (x1)
 - Wireless card protection cover (x1)
 - Wireless card protection cover fixing screw (x2)

Dimensions

Cautions: This drawing is not a scale.

Unit : mm

