

■Product summary

- Wireless connection (IEEE 802.11b/g) eliminates the need to connect any cables between the display and a PC.
- High-speed wireless transmission produce smooth motion images.
- Images from one PC can be displayed in real-time on as many as eight displays.
- Images from up to 16 PCs can be simultaneously displayed onto a single screen.
- Plasma displays can be controlled using a Web browser.
- The Wireless Presentation Board also accepts component video and audio inputs.

■Product specification (Design and specifications subject to change without notice)

Mass (Weight)	approx. 500 g (1.1 lbs)
Slot No.	2slots model : Slot 1+Slot 2 3slots model : Slot 1+Slot 2, Slot 2+Slot 3
Compliant	IEEE802.11b/g
Frequency band	2412~2462 MHz (1~11 channels)
Country	USA, Canada, Taiwan

- Accessories
- Terminal function label (1 sheet)
 - Terminal board replacement instructions
 - Slot cover fixing screw (x4)
 - Remote control (x1)
 - Dry batteries (AA x2)
 - CD-ROM (x1)
 - Wireless LAN card (x1)
 - Wireless card protection cover (x1)
 - Wireless card protection cover fixing screw (x2)

■Dimensions

Cautions: This drawing is not a scale.

Unit : mm
(inches)

