

出力の照度依存特性



REFERENCE

Dependence of Output on Illumination

1.Model : AM-1805

2.Outside Dimension : 55.0mm × 20.0mm

FL:White Fluorescent Light



*このデータは標準的な出力特性を示すものであり、特性を保証するものではありません。

*The data are meant to show standard electric characteristics only , not intended to guarantee the characteristics.


I - V Characteristics

REFERENCE

1.Model : AM-1805

2.Outside Dimension : 55.0mm × 20.0mm

FL:White Fluorescent Light



*このデータは標準的な出力特性を示すものであり、特性を保証するものではありません。

*The data are meant to show standard electric characteristics only , not intended to guarantee the characteristics.

出力の温度依存特性



REFERENCE

Dependence of Output on Temperature

1.Model : AM-1805

2.Outside Dimension : 55.0mm × 20.0mm

at 200Lx White Fluorescent Light



*このデータは標準的な出力特性を示すものであり、特性を保証するものではありません。



*The data are meant to show standard electric characteristics only , not intended to guarantee the characteristics.

Model : AM-1805C

1. Outside dimensions 外形寸法

Light Receiving Side (受光面)

Overcoat Side (オーバーコート面)



(dimension:mm)

Note

Glass Substrate Thickness (ガラス基板厚) : 1.1mm±0.1

Module Thickness (モジュール厚) : 1.3mmMAX

Accepts normal soldering for bending

(一般の半田を使用してリート*線付けが可能です。)

2. Rated Specifications (at 25℃)

Item	Specifications (Initial)		
2.1 Open circuit voltage: Voc 開放電圧	Typical	5.0V	at 200Lx FL
2.2 Short circuit Current: Isc 短絡電流	Typical	16.8μA	at 200Lx FL
2.3 Operating Voltage & Operating Current: Vope-lope 動作特性	Typical	2.6V - 3.85μA	at 50Lx FL
	Minimum	3.0V - 12.0μA	at 200Lx FL
	Typical	3.0V - 15.7μA	at 200Lx FL
2.5 Working temperature range: Topr 動作温度範囲	-10 to 60℃		
2.6 Storage temperature range: Tstg 保存温度範囲	-20 to 70℃		
2.7 Working illuminance range 使用照度範囲	~1000Lx		


FL: White Fluorescent Light

Model : AM-1805CA

1. Outside dimensions 外形寸法

Light Receiving Side (受光面)

Overcoat Side (オーバーコート面)



(dimension:mm)

Lead Wires : AWG30	
a:51	b:51

Note

Glass Substrate Thickness (ガラス基板厚) : $1.1 \text{ mm} \pm 0.1$ Module Thickness (モジュール厚) : 1.3 mm MAX Wire-Solder thickness: 2.5 mm MAX (including Module)
(リード線半田付け部厚)

2. Rated Specifications (at 25℃)

Item	Specifications (Initial)
2.1 Open circuit voltage: V_{oc} 開放電圧	Typical 5.0V at 200Lx FL
2.2 Short circuit Current: I_{sc} 短絡電流	Typical $16.8 \mu\text{A}$ at 200Lx FL
2.3 Operating Voltage & Operating Current: $V_{ope} - I_{ope}$ 動作特性	Typical 2.6V - $3.85 \mu\text{A}$ at 50Lx FL
	Minimum 3.0V - $12.0 \mu\text{A}$ at 200Lx FL
	Typical 3.0V - $15.7 \mu\text{A}$ at 200Lx FL
2.5 Working temperature range: T_{opr} 動作温度範囲	-10 to 60℃
2.6 Storage temperature range: T_{stg} 保存温度範囲	-20 to 70℃
2.7 Working illuminance range 使用照度範囲	~1000Lx

FL: White Fluorescent Light