


Panasonic

Ex 2G / Splash Proof

Panasonic Lighting - Product
Quality Testing



Learn more about
Panasonic lighting



Please contact

Panasonic®

All Rights Reserved © 2024 COPYRIGHT Panasonic Corporation Electric Works Company

LT63 2024.03

Specifications are subject to change without notice.

ISO 9001/14000

2024.03



I Series Lineup


Specification

Rated Voltage	220-240V
Frequency	50/60Hz
Lifetime	50,000 hours
CRI	80
Ambient Temperature Range	-20°C~40°C
Power Factor	0.9
Materials	Body: PC (White) Panel: PC (White)
IP Rating	IP65
Classification of Luminaries	Class II
SDCM	5



Dimension

2FT



Size : 600×85×60mm
Weight : 1.2kg

4FT



Size : 1212×85×60mm
Weight : 2.4kg

5FT



Size : 1500×85×60mm
Weight : 3.6kg

Ex 2G Splash Proof



Long Lifetime
50,000H




CRI
80




High Efficacy
128-144lm/W



IP Rating
IP65



Power Factor
0.9



Ambient Temperature
-20°C~40°C

Certification

RoHS / TISI

*Certification applicable for selected models.
*Spec and certification may change without notice.

I Data

Type	2FT (600mm)	4FT (1212mm)	5FT (1500mm)	
Wattage	18W	36W	45W	
Non Dimming	4000K ●	NNFC4034088 2300lm, 128lm/W	NNFC4034188 4600lm, 128lm/W	NNFC4034288 6500lm, 144lm/W
	6500K ●	NNFC4039088 2300lm, 128lm/W	NNFC4039188 4600lm, 128lm/W	NNFC4039288 6500lm, 144lm/W
Photometric Distribution				

cd/klm (I=100%)
— C0, C180
— C90, C270