


Panasonic

SP 2G / Splash Proof

Panasonic Lighting - Product
Quality Testing



Learn more about
Panasonic lighting



Please contact

Panasonic®

All Rights Reserved © 2024 COPYRIGHT Panasonic Corporation Electric Works Company

LT63 2024.03

Specifications are subject to change without notice.

ISO 9001/14000

2024.03



I Series Lineup

Specification


Rated Voltage	220-240V
Frequency	50/60Hz
Lifetime	25,000 hours
CRI	80
Ambient Temperature Range	-20°C~40°C
Power Factor	0.9
Materials	Body: PC (White) Panel: PC (White)
IP Rating	IP65
Classification of Luminaries	Class II
SDCM	5

2FT, 4FT, 5FT




Dimension

2FT




Size : 600×70×50mm
Weight : 1.0kg

4FT



Size : 1212×70×50mm
Weight : 2.1kg

5FT



Size : 1500×70×50mm
Weight : 3.1kg

SP 2G Splash Proof



Long Lifetime
25,000H




CRI
80




High Efficacy
100-111lm/W



IP Rating
IP65



Power Factor
0.9



Ambient Temperature
-20°C~40°C

Certification

RoHS / TISI

*Certification applicable for selected models.
*Spec and certification may change without notice.

I Data

Type	2FT (600mm)	4FT (1212mm)	5FT (1500mm)	
Wattage	18W	36W	45W	
Non Dimming	4000K ●	NNFC4033088 1800lm, 100lm/W	NNFC4033188 3600lm, 100lm/W	NNFC4033288 5000lm, 111lm/W
	6500K ●	NNFC4038088 1800lm, 100lm/W	NNFC4038188 3600lm, 100lm/W	NNFC4038288 5000lm, 111lm/W
Photometric Distribution				

cd/klm (I=100%)
— C0, C180
— C90, C270