


Panasonic

SP Downlight

Panasonic Lighting - Product
Quality Testing



Learn more about
Panasonic lighting



Please contact

Panasonic[®]

All Rights Reserved © 2024 COPYRIGHT Panasonic Corporation Electric Works Company

■ LT63 2024.06

Specifications are subject to change without notice.

ISO 9001/14000

2024.06



SP Downlight



Long Lifetime
30,000H




CRI
80



High Efficacy
100lm/W



IP Rating
IP44
*Water Proof Type Only



Power Factor
0.9

Certification

RoHS / SIRIM

*Certification applicable for selected models.
*Spec and certification may change without notice.

Series Lineup

Specification


Rated Voltage	220-240V
Frequency	50/60Hz
Lifetime	30,000 hours
CRI	80
Ambient Temperature Range	5°C~35°C
Power Factor	0.9
Materials	Body & Frame: PBT (White) Reflector: PC
IP Rating	IP20/44
SDCM	5*
Surge Resistant Voltage	10kV*

*Selected models




Dimension

9W




Size : Φ127×50mm
Cut-out size : Φ110mm
Weight : 0.10kg

12W




Size : Φ144×50mm
Cut-out size : Φ125mm
Weight : 0.12kg

15W



Size : Φ169×50mm
Cut-out size : Φ150mm
Weight : 0.18kg

24W



Size : Φ194×55mm
Cut-out size : Φ175mm
Weight : 0.33kg

Data

Wattage	9W	12W	15W	24W
Beam Angle	100°	100°	100°	100°
IP20	3000K ● NNNC7653105 900lm,100lm/W	—	NNNC7653305 1500lm,100lm/W	NNNC7653505 2400lm,100lm/W
	4000K ● —	—	NNNC7654305 1500lm,100lm/W	NNNC7654505 2400lm,100lm/W
IP44	3000K ● NNNC7663105 900lm,100lm/W	NNNC7663205 1200lm,100lm/W	—	—
	4000K ● —	—	—	—
Photometric Distribution				

cd/klm (I=100%)
— C0, C180
— C90, C270