




Certificates & Standards

RoHs / TISI

Dimension and Materials



Photometric Chart

| | |
|------------------------------|---------------------|
| Ref. No. | |
| Type of Luminaire | LED Tube |
| | G13 |
| | Tube |
| Set Model No. | BPT100S830TT |
| Type of Light Source | LED |
| Power Input | 10W |
| System Lumen Output | 1000 lm |
| System Efficacy | 100 lm/W |
| Power Voltage | 220-240V |
| Power Factor | 0.5 |
| Lifetime | 15000H(L70) |
| CCT | 3000K |
| CRI | 80 |
| SDCM | |
| Input Frequency | 50/60Hz |
| Dimming | non-Dimmable |
| Dimming Range | |
| UGR | |
| Glare Cut Angle | |
| Beam Angle | |
| Rotation Angle | |
| Tilt Angle | |
| IP code | 20 |
| IK code | |
| Ambient Temperature Range | 5 - 35°C |
| Surge Protection | |
| Classification of Luminaires | |
| THDi | |
| Effective Projected Area | |
| Driver | Integrated |
| Cut Out Size | |
| Dimensions | 28mm*604mm |
| Weight | 0.1 kg |
| Body | Glass |
| Reflector | |
| Diffuser | |
| Trim | |
| Casing | |
| Country of Origin | China |
| Brand | Panasonic |
| Remarks | |

Spec and certification may change without notice.

Others