


Panasonic



Certificates & Standards

RoHs

Dimension and Materials



| Height to lighted plane (m) | Initial beam center illuminance (lux) | Beam Diameter (mm) | Initial beam edge illuminance (lux) |
|-----------------------------|---------------------------------------|--------------------|-------------------------------------|
| 1 | 5,443 | 263 | 2,652 |
| 2 | 1,361 | 526 | 663 |
| 3 | 605 | 789 | 295 |

| | |
|------------------------------|--|
| Ref. No. | |
| Type of Luminaire | Downlight Glareless + Adjustable DL Ex-A Glareless Adjustable DL |
| Set Model No. | NNNC60131WLE88 |
| Type of Light Source | LED |
| Power Input | 10W |
| System Lumen Output | 700 lm |
| System Efficacy | 70 lm/W |
| Power Voltage | 220-240V |
| Power Factor | 0.9 |
| Lifetime | 50000H(L70) |
| CCT | 4000K |
| CRI | 80 |
| SDCM | |
| Input Frequency | 50/60Hz |
| Dimming | non-Dimmable |
| Dimming Range | |
| UGR | |
| Glare Cut Angle | 30deg. |
| Beam Angle | 15deg. |
| Rotation Angle | 355deg. |
| Tilt Angle | 23deg. |
| IP code | 20 |
| IK code | |
| Ambient Temperature Range | 5 - 35°C |
| Surge Protection | |
| Classification of Luminaires | Class II |
| THDi | |
| Effective Projected Area | |
| Driver | Integrated |
| Cut Out Size | 75mm |
| Dimensions | 85mm*94mm |
| Weight | 0.2 kg |
| Body | ADC(Gray) |
| Reflector | ADC12(Chrome) |
| Diffuser | PMMA(Transparent) |
| Trim | ADC12(White) |
| Casing | |
| Country of Origin | China |
| Brand | Panasonic |
| Remarks | |

Spec and certification may change without notice.

Others