


Panasonic



Certificates & Standards

RoHs

Dimension and Materials



Height to lighted plane (m)	Initial beam center illuminance (lux)	Beam Diameter (mm)	Initial beam edge illuminance (lux)
1	3,110	425	1,455
2	778	850	364
3	346	1,275	162

Ref. No.	
Type of Luminaire	Downlight Glareless + Adjustable DL Ex-A Glareless Adjustable DL
Set Model No.	NNNC60182WLE88
Type of Light Source	LED
Power Input	10W
System Lumen Output	660 lm
System Efficacy	66 lm/W
Power Voltage	220-240V
Power Factor	0.9
Lifetime	50000H(L70)
CCT	4000K
CRI	90
SDCM	
Input Frequency	50/60Hz
Dimming	non-Dimmable
Dimming Range	
UGR	
Glare Cut Angle	30deg.
Beam Angle	24deg.
Rotation Angle	355deg.
Tilt Angle	23deg.
IP code	20
IK code	
Ambient Temperature Range	5 - 35°C
Surge Protection	
Classification of Luminaires	Class II
THDi	
Effective Projected Area	
Driver	Integrated
Cut Out Size	75mm
Dimensions	85mm*94mm
Weight	0.2 kg
Body	ADC(Gray)
Reflector	ADC12(Chrome)
Diffuser	PMMA(Transparent)
Trim	ADC12(White)
Casing	
Country of Origin	China
Brand	Panasonic
Remarks	

Others

Spec and certification may change without notice.