Panasonic





| | |
|---|---|
| Ref. No. | |
| Type of Luminaire | Downlight |
| | Adjustable |
| | Adjustable DL |
| Set Model No. | **NNNC7629088** |


| | |
|---|---|
| Type of Light Source | LED |
| Power Input | 5W |
| System Lumen Output | 400 lm |
| System Efficacy | 80 lm/W |
| Power Voltage | 220-240V |
| Power Factor | 0.5 |
| Lifetime | 15000H(L70) |
| CCT | 4000K |
| CRI | 80 |
| SDCM | |
| Input Frequency | 50/60Hz |
| Dimming | non-Dimmable |
| Dimming Range | |
| UGR | |
| Glare Cut Angle | |
| Beam Angle | 60deg. |
| Rotation Angle | |
| Tilt Angle | |
| IP code | 20 |
| IK code | |
| Ambient Temperature Range | 5 - 35℃ |
| Surge Protection | |
| Classification of Luminaries | |
| THDi | |
| Effective Projected Area | |
| Driver | External |
| Cut Out Size | 80mm |
| Dimensions | L90mm*H43mm |
| Weight | 0.06 kg |
| Body | PBT(White) |
| Reflector | |
| Diffuser | PC(Transparent) |
| Trim | |
| Casing | |
| Country of Origin | China |
| Brand | Panasonic |
| Remarks | |

**Certificates & Standards**

RoHs / CR

Dimension and Materials



Photometric Chart

Spec and certification may change without notice.

Others

2026.10.15