



Panasonic



Certificates & Standards

RoHs / TISI

Dimension and Materials



Photometric Chart

| | |
|------------------------------|---|
| Ref. No. | |
| Type of Luminaire | Downlight Panel Light EZ-M Panel DL |
| Set Model No. | NNNC7651288 |
| Type of Light Source | LED |
| Power Input | 12W |
| System Lumen Output | 900 lm |
| System Efficacy | 75 lm/W |
| Power Voltage | 220-240V |
| Power Factor | 0.5 |
| Lifetime | 20000H(L70) |
| CCT | 6500K |
| CRI | 80 |
| SDCM | |
| Input Frequency | 50/60Hz |
| Dimming | non-Dimmable |
| Dimming Range | |
| UGR | |
| Glare Cut Angle | |
| Beam Angle | 100deg. |
| Rotation Angle | |
| Tilt Angle | |
| IP code | 20 |
| IK code | |
| Ambient Temperature Range | 5 - 35°C |
| Surge Protection | |
| Classification of Luminaires | Class II |
| THDi | |
| Effective Projected Area | |
| Driver | External |
| Cut Out Size | 110mm |
| Dimensions | 118mm*20mm |
| Weight | 0.15 kg |
| Body | ADC(White) |
| Reflector | |
| Diffuser | PS(Frost) |
| Trim | |
| Casing | |
| Country of Origin | China |
| Brand | Panasonic |
| Remarks | |

Others

Spec and certification may change without notice.