


Panasonic



Certificates & Standards

RoHs / TISI

Dimension and Materials



Photometric Chart

| | |
|------------------------------|---------------------|
| Ref. No. | |
| Type of Luminaire | Downlight |
| | Standard DL (Trade) |
| | DN 2G |
| Set Model No. | NNV70031WE1A |
| Type of Light Source | LED |
| Power Input | 9W |
| System Lumen Output | 720 lm |
| System Efficacy | 80 lm/W |
| Power Voltage | 220-240V |
| Power Factor | 0.5 |
| Lifetime | 20000H(L70) |
| CCT | 3000K |
| CRI | 80 |
| SDCM | |
| Input Frequency | 50/60Hz |
| Dimming | non-Dimmable |
| Dimming Range | |
| UGR | |
| Glare Cut Angle | |
| Beam Angle | |
| Rotation Angle | |
| Tilt Angle | |
| IP code | 20 |
| IK code | |
| Ambient Temperature Range | 5 - 35°C |
| Surge Protection | |
| Classification of Luminaires | Class II |
| THDi | |
| Effective Projected Area | |
| Driver | Integrated |
| Cut Out Size | 90mm |
| Dimensions | 109mm*32mm |
| Weight | 0.064 kg |
| Body | PP(White) |
| Reflector | |
| Diffuser | PC/PS(Frost) |
| Trim | PC+ABS (White) |
| Casing | |
| Country of Origin | China |
| Brand | Panasonic |
| Remarks | RG0 |

Spec and certification may change without notice.

Others