

Certificates & Standards

Dimension and Materials

Photometric Chart

| | |
|------------------------------|---|
| Ref. No. | |
| Type of Luminaire | Floodlight Standard Floodlight (Pro) Floodlight |
| Set Model No. | PFLM11703 |
| Type of Light Source | LED |
| Power Input | 70W |
| System Lumen Output | 7000 lm |
| System Efficacy | 100 lm/W |
| Power Voltage | 240V |
| Power Factor | 0.95 |
| Lifetime | 50000H(L70) |
| CCT | 3000K |
| CRI | 70 |
| SDCM | |
| Input Frequency | 50Hz |
| Dimming | non-Dimmable |
| Dimming Range | |
| UGR | |
| Glare Cut Angle | |
| Beam Angle | |
| Rotation Angle | |
| Tilt Angle | |
| IP code | 66 |
| IK code | |
| Ambient Temperature Range | |
| Surge Protection | |
| Classification of Luminaires | |
| THDi | |
| Effective Projected Area | |
| Driver | |
| Cut Out Size | |
| Dimensions | 265mm*283mm*60mm |
| Weight | 3 kg |
| Body | |
| Reflector | |
| Diffuser | Glass |
| Trim | |
| Casing | |
| Country of Origin | India |
| Brand | Panasonic |
| Remarks | |

Spec and certification may change without notice.

Others